

**Server Memory Compatibility Test Certificate**


Test System: **Supermicro X9SRE-F** Test Result: **Pass**

Leveraged System(s): X9SRA, X9SRi, X9SRI-F, X9SRE, X9SRG-F, X9SRW-F, X9SRW-3F

Module Specifications										Rev. 1/13/2015
<b>DIMM Vendor</b>	<b>DIMM Part Number</b>	<b>Type</b>	<b>Voltage</b>	<b>Size</b>	<b>Config.</b>	<b>Speed</b>	<b>CL</b>	<b>R/C</b>	<b>Rank</b>	
Kingston	KVR16LR11D8/8HD	RDIMM	1.35V	8GB	1Gx72	1600	11	B	DR	
<b>DRAM Vendor</b>	<b>DRAM Part Number</b>	<b>DRAM Density / Width / Date Code</b>			<b>Register Vendor / Rev.</b>		<b>DIMM Composition</b>			
Sk Hynix	H5TC4G83DFR-PBA	4Gb	512Mx8bit	1704	IDT	6.4	(512x8)*72			

System Configuration	
SETUP	System Information
AVL S/N	SO6530
System S/N	ZM23U39156
Board Rev. (PBA)	1.2
CPU Type	Intel E5-2650(IVB) x 1
Chipset	Intel C602
BIOS / Date	3.2 /8/31/2015
BMC / ME	2.14
FRU/SDR	n/a
OS	Red Hat Enterprise Linux 6.2 Kernel 2.6.32
Test Tool	SAT, Memory Stress v1077

Testing Summary		
Test Items	Test Description	Test Results
1. Latest BIOS Upgrade & Configuration check	Record memory Size and Speed detection from BIOS	Done
2. SPD Check	DIMM SPD content check for JEDEC compliance	Pass
3. Reset Cycle	1 DIMM Per Channel when applicable	Pass
4a. Memory Stress	DIMM Loading per spec	8 hours per config
4b. Memory Benchmark		5 loops per config
4c. Reset Cycle		200 loops per config
5. Functional Stress Test		12 hours
Note:		



AVL USE ONLY:							
Completed by:	Van Nguyen	Completion Date:	4/14/2017	AVL A#	11903	AVL W/O	WD7836
Comments:							